

Water Heater Heat Pump

RSJ-35/300RDN3-F1



Features

- Running ambient temperature -20~43°C
- Water output temperature 38~65°C
- Refrigerant R134a, environmentally friendly
- A rated energy efficiency
- Complete isolation between water and electricity, more safe
- Condenser coil is wrapped around the inner tank, no cross contamination potential
- Automatic weekly disinfect function
- Enamel tank, perfect anticorrosion performance
- 9 key LCD display panel
- Integral designed and just need to connect water pipes
- Flexible duct installation, 25Pa air flow pressure enables ducted length up to 10m













Dimensions





Specifications

Model			RSJ-35/300RDN3-F1	
Power supply V/Ph/Hz		220-240/1/50		
Heat Source			Economy	E-heater
Running ambient temperature		°C	-7~43	-20~43
Output water temperature		°C	Default 55,38~65	
Storage size		Ltr	300	
Capacity ⁱ		kW	3.00	3.00
COP			3.60	1.00
Max. current		A	6.5	13.0
Water heating energy efficien	cy class		Ä	
Dimension (D×H)		mm	Ф650×1,920	
Packing (W×H×D)		mm	750×2,150×780	
Net/gross weight		kg	145.5/175.5	
Sound pressure level		dB(A)	45	
Sound power level		dB(A)	58	
Compressor Type		Rotary		
Fan motor	Туре		AC Motor	
Air side heat exchanger Type		Fin-coil		
Water side heat exchanger	er side heat exchanger Type		Dividing wall type heat exchanger	
Refrigerant	Type/Quantity	kg	R134a/1.2	
	Throttle type		Electric expansion valve	
Water pipeline	Water inlet pipe	mm	DN20	
	Water outlet pipe	mm	DN20	
	Drainage pipe	mm	DN20	
	PTR valve joint	mm	DN20	
E-heater		kW	3	
Hot water yield		m³/h	0.086	
Applicable persons		5~6		

Remark:

- $1. The test conditions: outdoor temperature 15/12 ^{\circ}C (DB/WB), initial water temperature in the units is 15 ^{\circ}C, terminal water {\it tenture} is 45 ^{\circ}C.$
- 2. Sound pressure value test conditions: four side of the unit, distance is 1m, and height is 1m + half of the unit's height.
- 3. The above data test reference standard EN16147:2011; EN60379:2004; EN12103:2011; (EU)No:812:2013; (EU)No:814:2013.
- 4. The specifications may be changed for product improvement without notice.

Address: Unit A-110 Krisdale Commercial Center AC Cortes Ave., Mandaue City, Cebu 6014 Philippines

Tel: (032) 422 3155, (032) 505 4898

www.generalroyal.com.ph facebook: @generalroyalaircon

Note: Product specifications change from time to time as product improvements and developments are released and may vary from those in this document.